



DUMA VIDEO
Low Latency MPEG Codecs

Akali

Altera MPEG-2 Encoder FPGA IP

The Akali IP is optimized for very low latency video compression. The high density design allows for a single FPGA compression design, reducing overall system costs and power consumption. This makes Akali the IP choice for RF video links, industrial control, video conferencing, and surveillance.

The Duma Video team is dedicated solely to video compression and decompression. We were the first to have a working real-time HD solution on FPGA.

Design services are available upon request.

FEATURES

- Chroma 4:2:0 and 4:2:2
- Extensive search motion estimation
- I-Frame and IP-Frames GOP structure
- Selectable GOP length
- CBR / VBR selectable
- Frame rate: 3fps to 600fps
- Latency: 2 frames / 30 ms
- Video resolution: User defined up to 1080i/60fps
- Audio sample frequency: 32kHz, 44.1kHz, 48kHz
- Video and transport bit rates selectable from 1 Mb/s to 100 Mb/s
- Low power
- All code written by Duma Video
- Flexible licensing terms

SPECIFICATIONS

FPGAs supported	Stratix IV
License options	One-time fee or per unit royalty
Control interfaces	I2C, PCI, as well as proprietary interfaces
Audio/Video Interfaces	I2S, SMPTE 125m/274m, BT 656/601, DVI/HDMI and others
Physical size	1 chip
Operating temp	0 to 85 C

DUMA VIDEO

Phone: 360.859.4017 • Fax: 360.326.1747

E-mail: info@dumavideo.com • Web: www.dumavideo.com