



BMA-11-O

Omni-Directional Antenna

Features

Gain	11dBi min. (See table.)
Frequency	2.0-2.5 GHz
Polarization	Linear
Azimuth BW	360 degrees
Elevation BW	(See table.)
Impedance	50 Ω
RF Connector	N female
VSWR	1.5:1 max.
Weight	<10 lbs.
Dimensions	3.75" dia. x 50" long
Mounting Flange	5.0" dia. base x 1.25" to shoulder (0.50" through holes)
Mounting	0.25" thru hole, 4 places on 4.50" BC
Color	White
BMS Part Number	120601100

Available accessories include BLNA-202 low noise amplifier with power supply, filters, DC inserters, RF cable, etc.

Frequency	Elevation Beamwidth	Gain
2.00 GHz	8.50 degrees	11.30 dBi
2.25 GHz	7.50 degrees	11.80 dBi
2.50 GHz	7.00 degrees	12.30 dBi



Broadcast Microwave Services, LLC
12305 Crosthwaite Circle • Poway, CA 92064 • U.S.A.
Tel: +1-858-391-3050 • Toll Free (U.S.): 800-669-9667
Fax: +1-858-391-3049 • Website: www.bms-inc.com
E-mail: sales@bms-inc.com

Broadcast Microwave Services Europe GmbH & Co. KG
In Der Au 19 • 61440 Oberursel • Germany
Tel: +49-6124-7239-00 • Fax: +49-6124-7239-29
Website: www.bms-inc.com
E-mail: saleseurope@bms-inc.com

